



20
26



amster
bikes & parts

superior.



Geboren im Rennsport. Hergestellt in Tschechien.

Superior überschreitet seit über 30 Jahren Grenzen. Geboren und gebaut in Tschechien. werden unsere Fahrräder bei BikeFun International entwickelt und produziert.

Von den ersten Partnerschaften mit Legenden wie Bart Brentjens, über viele Weltcup-Siege mit jB BRUNEX Superior Factory Racing, bis hin zur heutigen Zusammenarbeit mit dem Olympiasieger Jaroslav Kulhavy - Racing liegt in unserer DNA. Diese Erfahrung steckt in jedem Rahmen, den wir bauen.

superior.

Inhaltsverzeichnis

Table des matières

ROAD

RR	03 - 06
XR GF	07

GRAVEL

XR Gravel	09 - 15
GA	16
iXR E-Gravel	17

E-MTB Full-Suspension

iXF (light e-Bike)	19 - 21
eXF	22 - 26

E-MTB Hardtail

eXP	28 - 29
-----	---------

E-TOUR Urban

iBLOX (light Urban e-Bike)	31 - 32
eBLOX	33 - 37

CITY e-Bikes

eWAY	39 - 40
------	---------

MTB Full-Suspension

XF RC Race	45 - 47
XF DC Trail	42 - 44

MTB Hardtail

XP	49 - 52
XC	53 - 61

JUNIOR

Junior 27.5"	63 - 67
Junior 24" & 20"	68 - 78

URBAN & TREKKING

BLOX City	80 - 83
-----------	---------



road

RR / XR GF

Superior Road-Bikes sind für Geschwindigkeit gebaut. Leichte Rahmen, steife Reaktion und präzises Handling verschaffen dir den entscheidenden Vorteil.

Egal ob Rennen oder Training - eines ist sicher: Du bist schneller als du denkst.

RR 9.8

Matte Carbon / Black

ROAD & GRAVEL / ROAD



UVP: CHF 4'999.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842209755	
520mm (S)	8592842209762	
540mm (M)	8592842209779	
560mm (L)	8592842209786	
580mm (XL)	8592842209793	

SPECIFICATION

BASE INFO

WEIGHT	7.50 kg
--------	---------

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP10x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready
TIRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race
TIRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
HANDLEBAR (MM)	380/70	380/90	400/100	400/100	420/100
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

RR 9.6

Matte Carbon / White

ROAD & GRAVEL / ROAD



UVP: CHF 3'999.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842209953	
520mm (S)	8592842209960	
540mm (M)	8592842209977	
560mm (L)	8592842209984	
580mm (XL)	8592842209991	

SPECIFICATION

BASE INFO

WEIGHT	8.00 kg
--------	---------

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable outing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP1.0x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Bazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready
TIRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race
TIRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
HANDLEBAR (MM)	380/70	380/90	400/100	400/100	420/100
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

RR 9.5

Matte Carbon / Black

ROAD & GRAVEL / ROAD



UVP: CHF 2'999.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842210058	
520mm (S)	8592842210065	
540mm (M)	8592842210072	
560mm (L)	8592842210089	
580mm (XL)	8592842210096	

SPECIFICATION

BASE INFO

WEIGHT	8.45 kg
--------	---------

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP1.0x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

RR 9.4

Gloss Red / White

ROAD & GRAVEL / ROAD



UVP: CHF 2'399.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842210300	
520mm (S)	8592842210317	
540mm (M)	8592842210324	
560mm (L)	8592842210331	
580mm (XL)	8592842210348	

SPECIFICATION

BASE INFO

WEIGHT	8.40 kg
--------	---------

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP1.0x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 6.5 GF

Gloss Black / White

ROAD & GRAVEL / GRAN FONDO



UVP: CHF 1'799.-

FRAME SIZE	EAN	Quantity
470mm (XS)	8592842215053	
490mm (S)	8592842215060	
510mm (M)	8592842215077	
530mm (L)	8592842215084	
550mm (XL)	8592842215091	
580mm (XXL)	8592842215107	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)	580mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	80	100	100	110	110
HANDLEBAR (MM)	410	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country



gravel

XR GR / GA / iXR

Superior Gravel-Bikes sind für Geschwindigkeit gebaut. Leichte Rahmen, steife Reaktion und präzises Handling verschaffen dir den entscheidenden Vorteil. Egal ob Rennen, Training oder beim erkunden - eines ist sicher: Du bist schneller als du denkst.

XR 9.9 GR

Gloss Black / Carbon

ROAD & GRAVEL / GRAVEL



UVP: CHF 7'899.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842215114	
520mm (S)	8592842215121	
540mm (M)	8592842215138	
560mm (L)	8592842215145	
580mm (XL)	8592842215152	
610mm (XXL)	8592842215169	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Hi Modulus Carbon Fork
BOTTOM BRACKET	SRAM DUB ROAD WIDE, PressFit, shell 41x86,5 mm
HEADSET	ACROS AIX-525R3S, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SRAM RED AXS, electronic shifter
SHIFTERS RIGHT	SRAM RED AXS, electronic shifter
REAR DERAILLEUR	SRAM RED XPLR AXS, 13 speed
CRANKSET	SRAM RED XPLR, DUB WIDE, 44T
CASSETTE	SRAM RED XPLR XG-1391, 13-speed, 10-46T
CHAIN	SRAM RED, Flattop 12s/13s, 120 Link

BRAKING SYSTEM

BRAKE FRONT	SRAM RED AXS, hydraulic disc brake
ROTOR FRONT	SRAM Paceline X, 160mm
BRAKE REAR	SRAM RED AXS, hydraulic disc brake
ROTOR REAR	SRAM Paceline X, 140mm

WHEELS

WHEELSET FRONT	DT Swiss GRC 1400 DICUT®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss GRC 1400 DICUT®, Carbon, CL, 12x142mm, XDR, Tubeless Ready
TIRE FRONT	Schwalbe G-One RS PRO Evo, Super Race, V-Guard, TL-Ready, 40-622, ADDIX Race
TIRE REAR	Schwalbe G-One RS PRO Evo, Super Race, V-Guard, TL-Ready, 40-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	LiteMOVE Rear Visibility Light, Red
------------	-------------------------------------

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	421	464	484	504	524	555
EFFECTIVE TOP TUBE LENGTH (MM)	523	535	545	574	595	616
STACK HEIGHT (MM)	524	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.8°	72.6°	72.6°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	994	995	1000	1016	1034	1048
HANDLEBAR (MM)	380/70	380/70	420/90	420/90	440/100	440/100
CRANKSET (MM)	165	165	170	172,5	172,5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.7 GR

Gloss Electric Purple / Grey

ROAD & GRAVEL / GRAVEL



UVP: CHF 4'699.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842215237	
520mm (S)	8592842215244	
540mm (M)	8592842215251	
560mm (L)	8592842215268	
580mm (XL)	8592842215275	
610mm (XXL)	8592842215282	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-52-01, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Mid Modulus Carbon Fork
BOTTOM BRACKET	SRAM DUB ROAD WIDE, PressFit, shell 41x86,5 mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black
REAR AXLE	SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS LEFT	SRAM FORCE AXS, electronic shifter
SHIFTERS RIGHT	SRAM FORCE AXS, electronic shifter
REAR DERAILLEUR	SRAM FORCE XPLR AXS, 13 speed
CRANKSET	SRAM FORCE XPLR, DUB WIDE, 44T
CASSETTE	SRAM FORCE XPLR XG-1391, 13-speed, 10-46T
CHAIN	SRAM FORCE, Flattop 12s/13s, 120 Link

BRAKING SYSTEM

BRAKE FRONT	SRAM FORCE AXS, hydraulic disc brake
ROTOR FRONT	SRAM Centerline X, 160mm
BRAKE REAR	SRAM FORCE AXS, hydraulic disc brake
ROTOR REAR	SRAM Centerline X, 140mm

WHEELS

WHEELSET FRONT	DT Swiss GRC 1600, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss GRC 1600, Carbon, CL, 12x142mm, XDR, Tubeless Ready
TIRE FRONT	Schwalbe G-One RS Performance, RaceGuard, TL-Ready, 40-622, ADDIX Eco
TIRE REAR	Schwalbe G-One RS Performance, RaceGuard, TL-Ready, 40-622, ADDIX Eco

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red
------------	-------------------------------------

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.5 GRA

Matte Trooper Green / Grey

ROAD & GRAVEL / GRAVEL



UVP: CHF 2'999.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842217156	
520mm (S)	8592842217163	
540mm (M)	8592842217170	
560mm (L)	8592842217187	
580mm (XL)	8592842217194	
610mm (XXL)	8592842217200	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-52-02, Carbon XR Adventure Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Adventure Mid Modulus Carbon Fork
BOTTOM BRACKET	SRAM DUB ROAD WIDE, PressFit, shell 41x86,5 mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS LEFT	SRAM RIVAL AXS, electronic shifter
SHIFTERS RIGHT	SRAM RIVAL AXS, electronic shifter
REAR DERAILLEUR	SRAM RIVAL XPLR AXS, 13 speed
CRANKSET	SRAM RIVAL XPLR, DUB WIDE, 44T
CASSETTE	SRAM RIVAL XPLR XG-1391, 13-speed, 10-46T
CHAIN	SRAM RIVAL, Flattop 12s/13s, 120 Link

BRAKING SYSTEM

BRAKE FRONT	SRAM RIVAL AXS, hydraulic disc brake
ROTOR FRONT	SRAM Paceline, 160mm
BRAKE REAR	SRAM RIVAL AXS, hydraulic disc brake
ROTOR REAR	SRAM Paceline, 140mm

WHEELS

WHEELSET FRONT	DT Swiss G 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss G 1800 SPLINE®, CL, 12x142mm, XDR, Tubeless Ready
TIRE FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red
------------	-------------------------------------

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 9.3 GRA

Gloss Dust / Dust

ROAD & GRAVEL / GRAVEL



UVP: CHF 2'499.-

FRAME SIZE	EAN	Quantity
490mm (XS)	8592842217217	
520mm (S)	8592842217224	
540mm (M)	8592842217231	
560mm (L)	8592842217248	
580mm (XL)	8592842217255	
610mm (XXL)	8592842217262	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-52-02, Carbon XR Adventure Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Adventure Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red
------------	-------------------------------------

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)	610mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XR 6.5 GR

Gloss Black / Matte Black

ROAD & GRAVEL / GRAVEL



UVP: CHF 1'899.-

FRAME SIZE	EAN	Quantity
470mm (XS)	8592842215596	
490mm (S)	8592842215602	
510mm (M)	8592842215619	
530mm (L)	8592842215626	
550mm (XL)	8592842215633	
580mm (XXL)	8592842215640	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)	580mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XR 6.3 GR

Brush Alu

ROAD & GRAVEL / GRAVEL



UVP: CHF 1'599.-

FRAME SIZE	EAN	Quantity
470mm (XS)	8592842215657	
490mm (S)	8592842215664	
510mm (M)	8592842215671	
530mm (L)	8592842215688	
550mm (XL)	8592842215695	
580mm (XXL)	8592842215701	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES U6030, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6030, 42T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO CUES U6030, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 160mm
BRAKE REAR	SHIMANO CUES U6030, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm,THRU Type AXLE
RIM FRONT	STARS J21DC, Disc, 28H
TIRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm,THRU Type AXLE
RIM REAR	STARS J21DC, Disc, 28H
TIRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)	580mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XR 6.3 GR

Gloss Electric Purple / Grey

ROAD & GRAVEL / GRAVEL



UVP: CHF 1'599.-

FRAME SIZE	EAN	Quantity
470mm (XS)	8592842215718	
490mm (S)	8592842215725	
510mm (M)	8592842215732	
530mm (L)	8592842215749	
550mm (XL)	8592842215756	
580mm (XXL)	8592842215763	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES U6030, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6030, 42T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO CUES U6030, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 160mm
BRAKE REAR	SHIMANO CUES U6030, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J21DC, Disc, 28H
TIRE FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J21DC, Disc, 28H
TIRE REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)	580mm (XXL)
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	410	410	410	430	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

GA 9.3

Gloss Black

ROAD & GRAVEL / GRAVEL



UVP: CHF 2'199.-

FRAME SIZE	EAN	Quantity
S	8592842221122	
M	8592842221139	
L	8592842221146	
XL	8592842221153	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	PD-FB-65E, Carbon Mid Modulus, BSA 68, Flat Mount 160, 12x142, UDH, ACROS headset, SP 27,2, Cable routing thru headset
FORK	GA Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS

DRIVETRAIN

SHIFTERS LEFT	SHIMANO GRX RX610, 2-speed
SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
FRONT DERAILLEUR	SHIMANO GRX FD-RX820, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO GRX RD-RX820, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 46-30T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J25D, Disc, Alloy, 32H
TIRE FRONT	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J25D, Disc, Alloy, 32H
TIRE REAR	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, Allroad Swift, Drop 129mm, Reach 65mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	72	72	72	72
SEAT TUBE LENGTH (MM)	500	520	540	560
EFFECTIVE TOP TUBE LENGTH (MM)	520	535	550	564
STACK HEIGHT (MM)	554	567	582	600
REACH (MM)	366	372	378	386
SEAT TUBE ANGLE	74.5°	74°	73.5°	73.5°
HEAD TUBE ANGLE	70°	70.5°	71°	71°
REAR CENTER (MM)	424	424	424	424
HEAD TUBE LENGTH (MM)	135	147	159	178
WHEELBASE (MM)	1019	1024	1030	1044
HANDLEBAR (MM)	420	420	440	440
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

iXR 6.5

Gloss Black / Matte Black

iGRAVEL | Light / iXR



UVP: CHF 3'999.-

FRAME SIZE	EAN	Quantity
470mm (XS)	8592842219129	
490mm (S)	8592842219136	
510mm (M)	8592842217286	
530mm (L)	8592842217293	
550mm (XL)	8592842217309	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote, Drop Bar

FRAMESET

FRAME	SU-E50-01, Alloy double-buttet , Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Bike packing and mudguards ready
SUSPENSION FORK	RockShox RUDY Base, Tapered, SoloAir, 12x100mm axle, 40mm travel
HEADSET	ACROS AZX-327R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	550	570	590
STACK HEIGHT (MM)	553	564	574	595	616
REACH (MM)	377	378	380	394	402
SEAT TUBE ANGLE	74,5°	74°	73,5°	73,5°	73°
HEAD TUBE ANGLE	70°	70,5°	70,5°	71°	71,5°
REAR CENTER (MM)	445	445	445	445	445
HEAD TUBE LENGTH (MM)	110	120	130	150	170
WHEELBASE (MM)	1039	1040	1045	1045	1070
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	170	170
SEATPOST (MM)	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



e-MTB fully

eXF / iXF

Vollgefederte E-MTBs vereinen zwei Welten: Leistungsstarke Modelle mit grossen Akkus und starken Bosch-Motoren für lange, anspruchsvolle Touren - und ultraleichte iXF-Modelle mit Carbonrahmen, kompaktem Antrieb und agiler Geometrie.

iXF 9.8

Matte Berry Carbon

iMTB FULL SUSPENSION | Light / iXF



UVP: CHF 8'999.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842202107	
17.5" (M)	8592842202114	
19" (L)	8592842202121	
21" (XL)	8592842202138	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h
WEIGHT	17.65 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down County Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535, Tapered, 15x110mm axle, 150mm travel
REAR SHOCK	DT Swiss R535, size 210x55mm, OL
HEADSET	ACROS AZX-596R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS POD 12-speed
REAR DERAILLEUR	SRAM X0 EAGLE AXS T-Type
CRANKSET	SRAM X0, BOSCH
CHAINRING	SRAM T-TYPE, 36T
CASSETTE	SRAM X0 XS-1295, 12-speed,T-Type, 10-52T
CHAIN	SRAM X0, T-Type

BRAKING SYSTEM

BRAKE FRONT	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR FRONT	SRAM HS2, 180mm
BRAKE REAR	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR REAR	SRAM HS2, 180mm

WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 12x148mm, SRAMXD, Tubeless Ready
TIRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TIRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SRAM AXS POD Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
HANDLEBAR (MM)	760/40	760/40	760/60	760/60
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L390/T125	L440/T150	L480/T170	L480/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

iXF 9.7

Gloss Chrome / Matte Carbon

iMTB FULL SUSPENSION | Light / iXF



UVP: CHF 6'999.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842215770	
17.5" (M)	8592842215787	
19" (L)	8592842215794	
21" (XL)	8592842215800	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Base Rush RC, Tapered, DebonAir+, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 210x55mm
HEADSET	ACROS AZX-327R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M826012, Wired
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TIRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

iXF 9.2

Gloss Teal / Teal Carbon

iMTB FULL SUSPENSION | Light / iXF



UVP: CHF 5'799.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842215855	
17.5" (M)	8592842215862	
19" (L)	8592842215879	
21" (XL)	8592842215886	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one pice link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PSYLO Silver RC, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 210x55mm
HEADSET	ACROS AZX-327R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stanless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	32	32	32	32
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 9049 B

Gloss Olive Metallic / Black

eMTB FULL SUSPENSION / eXF



UVP: CHF 5'399.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842183857	
17.5" (M)	8592842183864	
19" (L)	8592842183871	
21" (XL)	8592842183888	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh, Smart System
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	25.60 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Utralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated battery up to 750Wh, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535, Tapered, 15x110mm axle, 160mm travel
REAR SHOCK	DT Swiss R535, size 230x65mm, OL
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE XTSL-M8100-IR, RAPIDFIREPlus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 180mm
BRAKE REAR	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 180mm

WHEELS

WHEELSET FRONT	DT Swiss H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip
TIRE REAR	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-904A, 34.9mm, Full CNC machined, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L390/T125	L440/T150	L480/T170	L480/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 9019 B

Gloss Copper / Black

eMTB FULL SUSPENSION / eXF



UVP: CHF 4'299.-

FRAME SIZE	EAN	Quantity
17.5" (M)	8592842183949	
19" (L)	8592842183956	
21" (XL)	8592842183963	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh, Smart System
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	25.70 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated battery up to 750Wh, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Super Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-904A, 34.9mm, Full CNC mached, Black

GEOMETRY

FRAME SIZE	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27
SEAT TUBE LENGTH (MM)	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	610	630	650
STACK HEIGHT (MM)	625	625	625
REACH (MM)	465	485	505
SEAT TUBE ANGLE	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°
REAR CENTER (MM)	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120
WHEELBASE (MM)	1251	1271	1291
STEM (MM)	50	50	50
HANDLEBAR (MM)	760	760	760
CRANKSET (MM)	165	165	170
SEATPOST (MM)	L440/T150	L480/T170	L480/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 8089 B

Gloss Chrome / Black

eMTB FULL SUSPENSION / eXF



UVP: CHF 3'899.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842183970	
17.5" (M)	8592842183987	
19" (L)	8592842183994	
21" (XL)	8592842184007	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh, Smart System
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	25.15 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 4 For rough Off-Road riding and jumps less than 120cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Ultralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated battery up to 750Wh, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Nobby Nic Performance, 29x2.60
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Nobby Nic Performance, 29x2.60
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-617, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 8089 B SUV

Gloss Black / Black

eMTB FULL SUSPENSION / eXF



UVP: CHF 3'999.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842184014	
17.5" (M)	8592842184021	
19" (L)	8592842184038	
21" (XL)	8592842184045	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh, Smart System
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	28.50 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Utralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated battery up to 750Wh, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x57.5mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm,THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-617, 34.9mm, with Quick Release lever, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E 180lm
REAR LIGHT	AXA Juno
FENDER	Alloy

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	60	60	60	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	160	160	160	165
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eXF 8069 B SUV

Gloss Petrol / Black

eMTB FULL SUSPENSION / eXF



UVP: CHF 3'699.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842184052	
17.5" (M)	8592842184069	
19" (L)	8592842184076	
21" (XL)	8592842184083	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 500Wh, Smart System
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	28.55 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SUE03-CXBES3, Alu X6 Utralite MTB Trail, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated battery up to 750Wh, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RST Blade, 1.5", 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x57.5mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M5100-IR, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M5100, 11-speed, 11-51T
CHAIN	KMC e11T

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm,THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Johnny Watts Performance, 29x2.35", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-617, 34.9mm, with Quick Release lever, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E 180lm
REAR LIGHT	AXA Blueline
FENDER	Alloy

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	27	27	27	27
SEAT TUBE LENGTH (MM)	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	598	610	630	650
STACK HEIGHT (MM)	625	625	625	625
REACH (MM)	465	465	485	505
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	446	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120	120
WHEELBASE (MM)	1251	1251	1271	1291
STEM (MM)	60	60	60	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	160	160	160	165
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



e-MTB hardtail

eXP

Superior Hardtail E-Bikes bieten die perfekte Balance aus Power und Leichtigkeit. Das starke und vielseitige eXP kombiniert Bosch-Power, klares Design und Vielseitigkeit für Alltag, Tour oder leichte Abenteuer.

eXP 6.5

Matte Dark Chrome / Black

eMTB HARDTAIL / eXP



UVP: CHF 3'899.-

FRAME SIZE	EAN	Quantity
15,5" (S)	8592842216357	
17,5" (M)	8592842216364	
19" (L)	8592842216371	
21" (XL)	8592842216388	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	150km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	RockShox RECON Silver RL, Tapered, SoloAir, 15x110mm axle, 120mm travel
HEADSET	ACROS AZX-676, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 35mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE, 34.9mm, Black Matte

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1215	1215	1235	1264
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	L408/T125	L458/T150	L500/T170	L500/T170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



UVP: CHF 3'299.-

FRAME SIZE	EAN	Quantity
15,5" (S)	8592842216395	
17,5" (M)	8592842216401	
19" (L)	8592842216418	
21" (XL)	8592842216425	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	150km
MAX. TORQUE	90Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCR32, Air, Remote, Tapered, 15x110mm axle, 120mm travel
HEADSET	ACROS AZX-327R1, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Hurricane Performance, 29x2.25, ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Hurricane Performance, 29x2.25, ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1215	1215	1235	1264
STEM (MM)	60	60	60	60
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	170
SEATPOST (MM)	400	400	400	400



e-TOUR

iBLOX / eBLOX

Superior e-TOUR Bikes stehen für Komfort und Stil im Alltag mit elektrischer Leichtigkeit. Ob du die grosse Reichweite des e-BLOX oder die leichte Agilität des iBLOX bevorzugst, beide bieten sanfte Bosch-Unterstützung.



iBLOX 6.5

Gloss Dust

iTOUR | Light / iBLOX



UVP: CHF 3'499.-

COMPUTER VISUALIZATION

FRAME SIZE	EAN	Quantity
14" (XS)	8592842215947	
16" (S)	8592842215954	
18" (M)	8592842215961	
20" (L)	8592842215978	
22" (XL)	8592842215985	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E41-02, Alu 6061T6, Touring Geometry, Smooth Welding, Bosch system ready, removable integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZX-327R1, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	14" (XS)	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	365	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	550	570	590	610	630
STACK HEIGHT (MM)	632	642	651	660	670
REACH (MM)	369	386	403	421	438
SEAT TUBE ANGLE	74°	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°	69°
REAR CENTER (MM)	450	450	450	450	450
HEAD TUBE LENGTH (MM)	110	120	130	140	150
WHEELBASE (MM)	1081	1102	1123	1144	1165
STEM (MM)	70	70	70	90	90
HANDLEBAR (MM)	700	700	700	700	700
CRANKSET (MM)	160	160	165	170	170
SEATPOST (MM)	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

iBLOX 6.5 LS

Gloss Dust

iTOUR | Light / iBLOX



UVP: CHF 3'499.-

FRAME SIZE	EAN	Quantity
15" (S)	8592842216029	
16" (M)	8592842216036	
18" (L)	8592842216043	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E41-02, Alu 6061T6, Touring Geometry, Smooth Welding, Bosch system ready, removable integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZX-327R1, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO XT RD-M8130, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15" (S)	16" (M)	18" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	365	432	485
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	642	651	660
REACH (MM)	386	403	421
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	450	450	450
HEAD TUBE LENGTH (MM)	120	130	140
WHEELBASE (MM)	1102	1123	1144
STEM (MM)	70	70	70
HANDLEBAR (MM)	700	700	700
CRANKSET (MM)	160	165	170
SEATPOST (MM)	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.5

Matte Dark Chrome / Black

eTOUR / eBLOX



UVP: CHF 3'999.-

FRAME SIZE	EAN	Quantity
15,5" (S)	8592842216432	
17,5" (M)	8592842216449	
19" (L)	8592842216456	
21" (XL)	8592842216463	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	51	51	51	51
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	50
SEAT TUBE ANGLE	78°	77°	77°	78°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1195	1215	1235	1264
STEM (MM)	65	65	65	90
HANDLEBAR (MM)	700	700	700	700
CRANKSET (MM)	160	160	160	160
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.5 LS

Matte Dark Chrome / Black

eTOUR / eBLOX



UVP: CHF 3'999.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842216494	
18" (M)	8592842216500	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu 6061T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	65	65
HANDLEBAR (MM)	700	700
CRANKSET (MM)	160	160
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.3

Gloss Dust

eTOUR / eBLOX



UVP: CHF 3'399.-

FRAME SIZE	EAN	Quantity
15,5" (S)	8592842216517	
17,5" (M)	8592842216524	
19" (L)	8592842216531	
21" (XL)	8592842216548	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	150km
MAX. TORQUE	90Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Intuvia 100

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NX1 Tapered, Air, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	51	51	51	51
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	50
SEAT TUBE ANGLE	78°	77°	77°	78°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1195	1215	1235	1264
STEM (MM)	65	65	65	90
HANDLEBAR (MM)	700	700	700	700
CRANKSET (MM)	160	160	160	160
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.3 LS

Gloss Dust

eTOUR / eBLOX



UVP: CHF 3'399.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842216579	
18" (M)	8592842216586	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	150km
MAX. TORQUE	90Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 85Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Intuvia 100

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NX1 Tapered, Air, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	65	65
HANDLEBAR (MM)	700	700
CRANKSET (MM)	160	160
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

eBLOX 6.2 LS

Gloss Black

eTOUR / eBLOX



UVP: CHF 2'999.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842220446	
18" (M)	8592842220453	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	120km
MAX. TORQUE	75Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Intuvia 100

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NVX32, Tapered, 15x110mm axle, 100mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartridge, Tapered
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	16" (S)	18" (M)
BB DROP (MM)	51	51
SEAT TUBE LENGTH (MM)	393	431
EFFECTIVE TOP TUBE LENGTH (MM)	590	610
STACK HEIGHT (MM)	635	653
REACH (MM)	465	465
SEAT TUBE ANGLE	78,9°	77,5°
HEAD TUBE ANGLE	66°	66°
REAR CENTER (MM)	442	442
HEAD TUBE LENGTH (MM)	120	140
WHEELBASE (MM)	1205	1213
STEM (MM)	70	70
HANDLEBAR (MM)	700	700
CRANKSET (MM)	160	160
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



city e-Bikes

e-WAY

Die City-E-Bikes von Superior machen jede Fahrt zum stilvollen Erlebnis. Mit Bosch-Motoren, komfortorientierter Geometrie und smarten Features bieten sie eine leise, sanfte und entspannte Art, sich in der Stadt zu bewegen. Perfekt für den Weg zur Arbeit, Besorgungen oder entspanntes Cruisen.



COMPUTER VISUALIZATION

UVP: CHF 3'799.-

FRAME SIZE	EAN	Quantity
460mm (S)	8592842220576	
500mm (M)	8592842220583	
540mm (L)	8592842220590	
580mm (XL)	8592842220606	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h
WEIGHT	30.30 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, QR Type, 80mm travel
HEADSET	ONE PT-1866A-078-1, 1-1/8"-1.5", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO NEXUS SL-C7000-5, REVOSHIFT, 5-speed
CRANKSET	ONE Sport, Alloy
CHAINRING	Gates CARBON DRIVE CDX, 46T
CASSETTE	Gates CARBON DRIVE CDX, 34T
BELT	Gates CARBON DRIVE CDX

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	ONE, 36H, Disc, 3/8"x100x140mm, Nut Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO NEXUS SG-C7000-5D, 36H, CL, 135x187mm
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE FR-E04_01, 34.9mm, Black
PEDALS	Marwi SP-827

CITY/ SUV SET

FRONT LIGHT	Spanninga Axendo, 60 lux
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy
CARRIER	Alloy Carrier with MIK system

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	62	62	62	62
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	580	600	620	640
STACK HEIGHT (MM)	604	626	648	670
REACH (MM)	390	397	403	409
SEAT TUBE ANGLE	72,5°	72°	71,5°	71°
HEAD TUBE ANGLE	69°	69,8°	70,5°	71,2°
REAR CENTER(MM)	485	485	485	485
HEAD TUBE LENGTH (MM)	170	180	190	200
WHEELBASE (MM)	1127	1133	1139	1145
HANDLEBAR (MM)	620	620	620	620
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country



UVP: CHF 2'999.-

FRAME SIZE	EAN	Quantity
460mm (S)	8592842217750	
500mm (M)	8592842217767	
540mm (L)	8592842217774	
580mm (XL)	8592842217781	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 500Wh
DISTANCE	120km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h
WEIGHT	29.85 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, 1-1/8", QR Type, 50mm travel
HEADSET	ONE PT-1866A-078-2 1-1/8", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE, 44T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 36H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	SCALATO MONDANO, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	SCALATO MONDANO, 50-622, Reflective Tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 38mm rise, 31.8mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE FR-E04_01, 34.9mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	Spanninga Axendo, 30 lux
REAR LIGHT	Spanninga Pling XE
FENDER	Steel
CARRIER	Alloy Carrier with MIK system

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	62	62	62	62
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	580	600	620	640
STACK HEIGHT (MM)	604	626	648	670
REACH (MM)	390	397	403	409
SEAT TUBE ANGLE	72,5°	72°	71,5°	71°
HEAD TUBE ANGLE	69°	69,8°	70,5°	71,2°
REAR CENTER (MM)	485	485	485	485
HEAD TUBE LENGTH (MM)	170	180	190	200
WHEELBASE (MM)	1127	1133	1139	1145
HANDLEBAR (MM)	620	620	620	620
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)	300	300	300	300



MTB fully

XF RC / XF DC

Das Superior XF bietet volle Kontrolle und Flow. Mit vollgefederter Rahmenplattform, cleverer Geometrie und Top-Komponenten gibt es dir Sicherheit - selbst in den härtesten Passagen. Schnell, verspielt und bereit für jedes Rennen - oder einfach perfekt für puren Trailspass.

XF 9.9 Team

Red Carbon / Matte Carbon

MTB FULL-SUSPENSION / XF TEAM



UVP: CHF 8'999.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842207379	
17.5" (M)	8592842204378	
19" (L)	8592842207386	
21" (XL)	8592842207393	

SPECIFICATION

BASE INFO

WEIGHT	10.90 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110-120 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm, ODL
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SW-M9250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9250, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9200, 34T
CASSETTE	SHIMANO XTR CS-M9200, 12-speed, 10-51T
CHAIN	SHIMANO XTR CN-M9100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XTR M9200, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL900, 180mm
BRAKE REAR	SHIMANO XTR M9200, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL900, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Rick Evo, TL-Ready, XC Pro, 29x2.4", ADDIX Speed
TIRE REAR	Schwalbe Rick Evo, TL-Ready, XC Pro, 29x2.4", ADDIX Speed

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X1, Carbon
SEATPOST LEVER	SRAM AXS POD, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
HANDLEBAR (MM)	760/60	760/60	760/80	760/80
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L390/T125	L390/T125	L440/T150	L440/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XF 9.7 RC

Matte Carbon / Smoke Chrome

MTB FULL-SUSPENSION / XF RC



UVP: CHF 6'299.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842207409	
17.5" (M)	8592842207416	
19" (L)	8592842207423	
21" (XL)	8592842207430	

SPECIFICATION

BASE INFO

WEIGHT	12.00 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110-120 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm, ODL
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644S, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XT SW-M8250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8200, 34T
CASSETTE	SHIMANO XT CS-M8200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

XF 9.2 RC

Matte Carbon / White

MTB FULL-SUSPENSION / XF RC



UVP: CHF 3'799.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842202008	
17.5" (M)	8592842202015	
19.0" (L)	8592842202022	
21.0" (XL)	8592842202039	

SPECIFICATION

BASE INFO

WEIGHT	13.35 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm

FRAMESET

FRAME	SU-01, Carbon MTB Race Pro, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm, ODL
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT 54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT 54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31.8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
BB DROP (MM)	40	40	40	40
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
STACK HEIGHT (MM)	579	589	597	607
REACH (MM)	427	449	465	482
SEAT TUBE ANGLE	74,9°	74,7°	74,6°	74,5°
HEAD TUBE ANGLE	68°	68°	68°	68°
REAR CENTER (MM)	428	428	428	428
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1124	1149	1169	1189
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	175	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

XF 9.6 DC

Gloss Grey / Light Grey

MTB FULL-SUSPENSION / XF DC



UVP: CHF 4'799.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842207812	
17.5" (M)	8592842207829	
19" (L)	8592842207836	
21" (XL)	8592842207843	

SPECIFICATION

BASE INFO

WEIGHT	13.20 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-01.2, Carbon MTB DC , Advanced Down Country Geometry, Travel 130 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TIRE FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready
TIRE REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

XF 6.6 DC

Matte Green Grey

MTB FULL-SUSPENSION / XF DC



UVP: CHF 3'599.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842208925	
17.5" (M)	8592842208932	
19" (L)	8592842208949	
21" (XL)	8592842208956	

SPECIFICATION

BASE INFO

WEIGHT	13.95 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8200, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

XF 6.2 DC

Gloss Olive

MTB FULL-SUSPENSION / XF DC



UVP: CHF 2'999.-

FRAME SIZE	EAN	Quantity
15.5" (S)	8592842220675	
17.5" (M)	8592842220682	
19" (L)	8592842220699	
21" (XL)	8592842220705	

SPECIFICATION

BASE INFO

WEIGHT	15.40 kg
--------	----------

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat postready.
SUSPENSION FORK	RockShox PSYLO Silver RC, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H,Tubeless Ready
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H,Tubeless Ready
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country



MTB hardtail

XP / XC

Die Hardtails Superior XP und XC bieten eine gelungene Mischung aus Leichtigkeit, Komfort und sicherem Handling. Ob im Rennen oder bei der Wochenendtour - diese Bikes stehen für Effizienz, Fahrspass und Genuss für alle.



XP 9.6

Matte Dark Chrome / Carbon

MTB HARDTAIL / XP



UVP: CHF 3'499.-

COMPUTER VISUALIZATION

FRAME SIZE	EAN	Quantity
13,5" (XS)	8592842213554	
15.5" (S)	8592842213561	
17.5" (M)	8592842213578	
19" (L)	8592842213585	
21" (XL)	8592842213592	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus,Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644S, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, LightBlack

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7100, Hollowtech II, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

WHEELSET FRONT	DT Swiss X 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss X 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	13,5" (XS)	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	57	57	57	57	57
SEAT TUBE LENGTH (MM)	30	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	645
STACK HEIGHT (MM)	599	599	603	613	622
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	75,9°	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430	430
HEAD TUBE LENGTH (MM)	90	90	95	105	115
WHEELBASE (MM)	1127	1147	1169	1193	1217
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	350	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 9.1

Gloss Grey

MTB HARDTAIL / XP



UVP: CHF 1'999.-

COMPUTER VISUALIZATION

FRAME SIZE	EAN	Quantity
13,5" (XS)	8592842216890	
15.5" (S)	8592842216906	
17.5" (M)	8592842216913	
19" (L)	8592842216920	
21" (XL)	8592842216937	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus,Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ray Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	13,5" (XS)	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	57	57	57	57	57
SEAT TUBE LENGTH (MM)	30	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	645
STACK HEIGHT (MM)	599	599	603	613	622
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	75,9°	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430	430
HEAD TUBE LENGTH (MM)	90	90	95	105	115
WHEELBASE (MM)	1127	1147	1169	1193	1217
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	170	170	170	175	175
SEATPOST (MM)	350	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 6.6

Brushed Teal / Teal

MTB HARDTAIL / XP



UVP: CHF 1'699.-

FRAME SIZE	EAN	Quantity
13,5" (XS)	8592842212717	
15.5" (S)	8592842212724	
17.5" (M)	8592842212731	
19" (L)	8592842212748	
21" (XL)	8592842212755	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, UDH dropout, Boost Thru axle 148x12mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8100, Hollowtech II, 32T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	13,5" (XS)	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	303	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	642
STACK HEIGHT (MM)	611	611	620	629	639
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	76,2°	75,8°	75°	75,7°	77°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	432	432	432	432	432
HEAD TUBE LENGTH (MM)	90	90	100	110	120
WHEELBASE (MM)	1130	1150	1174	1198	1222
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XP 6.2

Gloss Brush Alu / Black

MTB HARDTAIL / XP



UVP: CHF 1'399.-

FRAME SIZE	EAN	Quantity
13,5" (XS)	8592842212816	
15.5" (S)	8592842212823	
17.5" (M)	8592842212830	
19" (L)	8592842212847	
21" (XL)	8592842212854	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, UDH dropout, Boost Thru axle 148x12mm
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 120mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	STARS R27-1M,Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ray Performance, 29x2.25", ADDX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M,Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	13,5" (XS)	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	303	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	642
STACK HEIGHT (MM)	611	611	620	629	639
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	76,2°	75,8°	75°	75,7°	77°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	432	432	432	432	432
HEAD TUBE LENGTH (MM)	90	90	100	110	120
WHEELBASE (MM)	1130	1150	1174	1198	1222
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	170	170	170	175	175
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.



superior.

XC 6.9

Gloss Black

MTB HARDTAIL / XC



UVP: CHF 999.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842213066	
18" (M)	8592842213073	
20" (L)	8592842213080	
22" (XL)	8592842213097	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 120mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XC 6.9

Gloss Dust

MTB HARDTAIL / XC



UVP: CHF 999.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842213103	
18" (M)	8592842213110	
20" (L)	8592842213127	
22" (XL)	8592842213134	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QR Type, 120mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 6.9 MS

Matte Soft Violet

MTB HARDTAIL / XC



UVP: CHF 999.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842213387	
18" (M)	8592842213394	
20" (L)	8592842213400	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRtype, 120mm travel
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRtype
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
STEM (MM)	60	60	60
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XC 6.5

Gloss Dust

MTB HARDTAIL / XC



UVP: CHF 899.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842214742	
18" (M)	8592842214759	
20" (L)	8592842214766	
22" (XL)	8592842214773	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 120mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XC 6.5 MS

Gloss Black / Copper

MTB HARDTAIL / XC



UVP: CHF 899.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842213417	
18" (M)	8592842213424	
20" (L)	8592842213431	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 120mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
STEM (MM)	60	60	60
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XC 6.2

Gloss Grey / Petrol

MTB HARDTAIL / XC



UVP: CHF 849.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842213264	
18" (M)	8592842213271	
20" (L)	8592842213288	
22" (XL)	8592842213295	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 120mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 6.1

Matte Dark Red

MTB HARDTAIL / XC



UVP: CHF 749.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842219327	
18" (M)	8592842219402	
20" (L)	8592842219488	
22" (XL)	8592842219556	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QRTYPE, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	170	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

XC 6.1 MS

Matte Purple

MTB HARDTAIL / XC



UVP: CHF 749.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842219334	
18" (M)	8592842219419	
20" (L)	8592842219495	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QRTYPE, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

XC 6.0

Matte Dark Chrome

MTB HARDTAIL / XC



UVP: CHF 679.-

FRAME SIZE	EAN	Quantity
16" (S)	8592842219310	
18" (M)	8592842219396	
20" (L)	8592842219471	
22" (XL)	8592842219549	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QRTYPE, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ESSA RD-U2000, Shadow Design
CRANKSET	ONE Sport, Alloy, 34T
CASSETTE	Shimano HG300, 11-45T
CHAIN	KMC NS8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Rubena Cheetah, 29x2,1"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QRType
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Rubena Cheetah, 29x2,1"
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.



junior

TEAM / F.L.Y. / RACER

Superior Kinderbikes stehen für Sicherheit, Kontrolle und Fahrspass. Leichte Rahmen, komfortable Geometrie und zuverlässige Komponenten geben jungen Fahrern Vertrauen und Freude bei jeder Fahrt - vom ersten Pedaltritt an.

TEAM 27.7

Gloss Brushed Alu / Red

JUNIOR / TEAM



UVP: CHF 1'299.-

FRAME SIZE	EAN	Quantity
13" (XS)	8592842217316	
15.5" (S)	8592842218641	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru axle 148x12mm, Inner cable routing.
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	SB01, TA12x171.5, M12xP1.5x15.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 160mm

WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 28H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm
HANDLEBAR	ONE, Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
STACK HEIGHT (MM)	562	562
REACH (MM)	384	425
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	420	420
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1058	1099
STEM (MM)	50	50
HANDLEBAR (MM)	620	620
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

TEAM 27.3

Gloss Brushed Alu / Red

JUNIOR / TEAM



UVP: CHF 949.-

FRAME SIZE	EAN	Quantity
13" (XS)	8592842218610	
15,5" (S)	8592842218634	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QR Type, 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6050-10R, SHORT REACH, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm
HANDLEBAR	ONE, Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13" (XS)	15,5" (S)
BB DROP (MM)	45	45
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	567	567
REACH (MM)	384	423
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1070	1109
STEM (MM)	50	50
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

TEAM 27.3

Gloss Brushed Alu / Rainbow Black

JUNIOR / TEAM



UVP: CHF 949.-

FRAME SIZE	EAN	Quantity
13" (XS)	8592842217323	
15,5" (S)	8592842218627	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6050-10R, SHORT REACH, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QRType
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDX
HUB REAR	ONE Sport, 28H, CL, M10x135, QRType
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm
HANDLEBAR	ONE, Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	13" (XS)	15,5" (S)
BB DROP (MM)	45	45
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	567	567
REACH (MM)	384	423
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1070	1109
STEM (MM)	50	50
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

RACER 27

Gloss Racing Red

JUNIOR / RACER



UVP: CHF 599.-

FRAME SIZE	EAN	Quantity
13" (XS)	8592842218306	
15.5" (S)	8592842218313	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
SUSPENSION FORK	SR Suntour XCT30, 1-1/8", Coil, QRTYPE, 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J20S, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QRType
RIM REAR	STARS J20S, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 34mm rise, 25.4mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 27"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	435	435
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
STEM (MM)	35	35
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

RACER 27

Matte Radioactive Yellow

JUNIOR / RACER



UVP: CHF 599.-

FRAME SIZE	EAN	Quantity
13" (XS)	8592842218344	
15.5" (S)	8592842218658	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
SUSPENSION FORK	SR Suntour XCT30, 1-1/8", Coil, QRTYPE, 100mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J20S, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QRType
RIM REAR	STARS J20S, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 34mm rise, 25.4mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 27"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	435	435
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
STEM (MM)	35	35
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

TEAM 24

Gloss Brushed Alu / Red

JUNIOR / TEAM



UVP: CHF 799.-

FRAME SIZE	EAN	Quantity
11"	8592842218276	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	RST Aerial Air, 1-1/8", 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, SHORT REACH, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4010, Shadow Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QRType
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDX
HUB REAR	ONE Sport, 20H, CL, M10x135, QRType
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	503
REACH (MM)	356
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	393
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	40
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

TEAM 24

Gloss Brushed Alu / Rainbow Black

JUNIOR / TEAM



UVP: CHF 799.-

FRAME SIZE	EAN	Quantity
11"	8592842218269	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	RST Aerial Air, 1-1/8", 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, SHORT REACH, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4010, Shadow Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	503
REACH (MM)	356
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	393
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	40
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

TEAM 20

Gloss Brushed Alu / Red

JUNIOR / TEAM



UVP: CHF 699.-

FRAME SIZE	EAN	Quantity
9"	8592842217330	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QRType
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QRType
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	40
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

TEAM 20

Gloss Brushed Alu / Rainbow Black

JUNIOR / TEAM



UVP: CHF 699.-

FRAME SIZE	EAN	Quantity
9"	8592842217347	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult/t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QRType
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QRType
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	40
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.



UVP: CHF 699.-

FRAME SIZE	EAN	Quantity
11"	8592842217361	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult/t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QRType
RIM FRONT	STARS J20S, Disc, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QRType
RIM REAR	STARS J20S, Disc, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Redals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	470
REACH (MM)	365
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	391
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	968
STEM (MM)	40
CRANKSET (MM)	127
SEATPOST (MM)	300

F.L.Y. 24

Gloss Purple

JUNIOR / F.L.Y.



UVP: CHF 699.-

FRAME SIZE	EAN	Quantity
11"	8592842217972	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Alhonga HJ-372F, hydraulic disc brake
ROTOR FRONT	Alhonga, 140mm
BRAKE REAR	Alhonga HJ-372F, hydraulic disc brake
ROTOR REAR	Alhonga, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	470
REACH (MM)	365
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	391
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	968
STEM (MM)	40
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

F.L.Y. 20 VB

JUNIOR / F.L.Y.

Matte Teal



UVP: CHF 539.-

FRAME SIZE	EAN	Quantity
9"	8592842217958	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, V-Brake mount
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	microSHIFT TS39-7R, ThumpTap, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG200, 7-speed, 12-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 20H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 20H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
HUB REAR	ONE Sport, 20H, M10x130, QR Type
RIM REAR	STARS J19SZ, 20H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	40
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

RACER 24

Gloss Racing Red

JUNIOR / RACER



UVP: CHF 479.-

FRAME SIZE	EAN	Quantity
11"	8592842218283	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult/t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCT JR24, 1-1/8", Soft Spring, QR Type, 50mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE CH919TBW 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	35
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.

For availability and prices, please contact the retailers in your city/country

superior.

RACER 24

Matte Radioactive Yellow

JUNIOR / RACER



UVP: CHF 479.-

FRAME SIZE	EAN	Quantity
11"	8592842218290	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCT JR24, 1-1/8",Soft Spring, QR Type, 50mm travel
BOTTOM BRACKET	Thun lbex, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	35
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

RACER 20

Gloss Racing Red

JUNIOR / RACER



UVP: CHF 429.-

FRAME SIZE	EAN	Quantity
9"	8592842218320	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	35
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.

For availability and prices, please contact the retailers in your city/country

superior.

RACER 20

Matte Radioactive Yellow

JUNIOR / RACER



UVP: CHF 429.-

FRAME SIZE	EAN	Quantity
9"	8592842218337	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult\
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE CH919TBW, 1-1/8

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 15°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	35
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.



trekking & city

BLOX

Die BLOX-Bikes von Superior sind die ideale Wahl für entspannte Fahrten in und um die Stadt. Voll ausgestattet mit Licht, Schutzblechen und Gepäckträgern - bereit für den Alltag und Wochenendabenteuer. Praktische Bikes mit klarem Design und Komfort im Fokus.

BLOX 6.7 T

Gloss Metallic Black

TREKKING / CITY



UVP: CHF 1'279.-

FRAME SIZE	EAN	Quantity
410mm (S)	8592842216944	
460mm (M)	8592842216951	
510mm (L)	8592842216968	
560mm (XL)	8592842216975	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-HLO, 1-1/8", Coil, QR Type, 50mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U6000-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U6010-L, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6010, Hollowtech II, 46-32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE, 31.8mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	AXA BlueLine 30, 30 lx
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy

GEOMETRY

FRAME SIZE	410mm (S)	460mm (M)	510mm (L)	560mm (XL)
BB DROP (MM)	70	70	70	70
SEAT TUBE LENGTH (MM)	410	460	510	560
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	592	610	610	630
REACH (MM)	400	415	435	450
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	460	460	460	460
HEAD TUBE LENGTH (MM)	140	160	160	180
WHEELBASE (MM)	1087	1109	1129	1150
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	660	660	660	660
CRANKSET (MM)	170	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

BLOX 6.7 T MS

Gloss Metallic Black

TREKKING / CITY



UVP: CHF 1'279.-

FRAME SIZE	EAN	Quantity
380mm (S)	8592842216982	
460mm (M)	8592842216999	
500mm (L)	8592842217002	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-HLO, 1-1/8", Coil, QR Type, 50mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U6000-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U6010-L, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6010, Hollowtech II, 46-32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31.8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE, 31.8mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	AXA BlueLine 30, 30 lx
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy

GEOMETRY

FRAME SIZE	380mm (S)	460mm (M)	500mm (L)
BB DROP (MM)	70	70	70
SEAT TUBE LENGTH (MM)	380	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	592	610	629
REACH (MM)	400	414	429
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°
REAR CENTER (MM)	460	460	460
HEAD TUBE LENGTH (MM)	140	160	180
WHEELBASE (MM)	1087	1109	1130
STEM (MM)	70	70	90
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

BLOX 6.5 T

Gloss Dust

TREKKING / CITY



UVP: CHF 849.-

FRAME SIZE	EAN	Quantity
410mm (S)	8592842217019	
460mm (M)	8592842217026	
510mm (L)	8592842217033	
560mm (XL)	8592842217040	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QRType, 50mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U4000-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U4000,Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U4020, Shadow Design
CRANKSET	SHIMANO CUES FC-U4010-2, 46-30T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE, 31.8mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	AXA BlueLine 30, 30 lx
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy

GEOMETRY

FRAME SIZE	410mm (S)	460mm (M)	510mm (L)	560mm (XL)
BB DROP (MM)	70	70	70	70
SEAT TUBE LENGTH (MM)	410	460	510	560
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	592	610	610	630
REACH (MM)	400	415	435	450
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	460	460	460	460
HEAD TUBE LENGTH (MM)	140	160	160	180
WHEELBASE (MM)	1087	1109	1129	1150
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	660	660	660	660
CRANKSET (MM)	170	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

BLOX 6.5 T MS

Gloss Dust

TREKKING / CITY



UVP: CHF 849.-

FRAME SIZE	EAN	Quantity
380mm (S)	8592842217057	
460mm (M)	8592842217064	
500mm (L)	8592842217071	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QRType, 50mm travel
BOTTOM BRACKET HEADSET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm FSA NO.80, ICR, Semi-Cartridge, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U4000-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U4000,Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U4020, Shadow Design
CRANKSET	SHIMANO CUES FC-U4010-2, 46-30T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Delta Cruiser Plus, PunctureGuard, TwinSkin, 47-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE, 31.8mm, Black
PEDALS	Marwi SP-823

CITY/ SUV SET

FRONT LIGHT	AXA BlueLine 30, 30 lx
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy

GEOMETRY

FRAME SIZE	380mm (S)	460mm (M)	500mm (L)
BB DROP (MM)	70	70	70
SEAT TUBE LENGTH (MM)	380	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	592	610	629
REACH (MM)	400	414	429
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°
REAR CENTER (MM)	460	460	460
HEAD TUBE LENGTH (MM)	140	160	180
WHEELBASE (MM)	1087	1109	1130
STEM (MM)	70	70	90
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.

Geschwindigkeit, Leichtigkeit und Klarheit - das ist der Spirit der Marke Superior. Diese drei Werte stecken in jedem Modell, das wir entwickeln. Unsere Bikes werden intern designt, unter realen Bedingungen getestet und mit Liebe zum Detail gebaut. Gestützt auf Rennerfahrung, smarte Technik und ehrliches Handwerk - das macht Superior zur richtigen Wahl. Ob Racebike, E-Bike oder City-Bike - dieselben Werte gelten für das gesamte Sortiment.

Der Geist in jedem Bike



superior.

superior.



Ihr Fachhändler // Votre Marchand

Hergestellt und gedruckt in der Schweiz.
Alle Angaben entsprechen dem Stand bei Drucklegung.

Irrtümer, Fehler und Änderungen vorbehalten.
Alle angegebenen Preise sind unverbindliche Empfehlungen.

Sous réserve de modification de prix et modèle.
Tous les prix indiqués sont des recommandations sans engagement.